TECHNICAL DATA SHEET

safeguard®

# MW19 Mill Wound Steel Strapping

| | |
|---|---|
| **Product data** | |
| ~ surface finish | black painted and waxed, deburred edges |
| ~ winding | oscillated |
| ~ strap width | 19.0 mm |
| ~ width tolerance | +/- 0.20 mm |
| ~ strap thickness | 0.5 mm |
| ~ thickness tolerance | +/- 0.03 mm |
| ~ strap length on coil | 675 mtr |
| ~ coil inside diameter | 406 mm |
| ~ coil outside diameter | 600 mm (approx.) |
| ~ coil weight | 50 kg (approx.) |
| ~ coils per pallet | 12 |
| | |
| **Technical data** | |
| ~ tensile strength (minimum) | 800 N/mm² |
| ~ tensile strength (average) | 900 N/mm² |
| ~ breaking strain (minimum) | 7600 N |
| ~ breaking strain (average) | 8550 N |
| ~ elongation, A5 (average) | 7.0% |
| ~ elongation, A100 (minimum) | 1.0% |
| ~ elongation, A100 (average) | 2.5% |

*All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.*
*Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose.*
*The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.*