TECHNICAL DATA SHEET



PCT50-W White Cloth Tape

Product description	Self-adhesive polycloth duct tape
rioduct description	Used for sealing, insulation, packaging, masking and repair
	General purpose interior and exterior use
	General purpose interior and exterior use
Product data	
~ roll width	50mm
~ roll length	50mtr
~ material	Woven polyester and coated cotton blended with LDPE
~ adhesive	Synthetic rubber
Technical data	
~ total thickness	0.17mm (+/- 5%)
~ adhesion to steel	18N per 25mm
~ tensile strength	75N per 25mm
~ rolling ball tack	> 12 (ball no.)
~ holding power	> 3 hours
~ service temp. range	-15 C to +60 C
sei nee tempi range	
Application	Optimum adhesion is achieved after a 24 hour bonding period in a
	constant ambient temperature of +23 C if:
	~ surfaces are clean, and free from grease and dust
	~ the tape is applied at temperatures between 0 C and +35 C
	~ contact with the exposed adhesive is avoided
	~ maximum pressure is used during application
Storage and shelf life	Kept in clean, dry, well-ventilated conditions and an ambient temperature
	of +10 C to +30 C, the shelf life will be a minimum of 12 months
Packaging data	
~rolls per case	24
~ case weight	14kg
All information and recommendations are provided to the	

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience.

Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.