TECHNICAL DATA SHEET



PCT75-B Black Cloth Tape

Product description	Self-adhesive polycloth duct tape
rioduct description	Used for sealing, insulation, packaging, masking and repair
	General purpose interior and exterior use
	General purpose interior and exterior use
Product data	
~ roll width	75mm
~ roll length	50mtr
~ material	Woven polyester and coated cotton blended with LDPE
~ αdhesive	Synthetic rubber
Technical data	
~ total thickness	0.17mm (+/- 5%)
~ adhesion to steel	18N per 25mm
~ tensile strength	75N per 25mm
~ rolling ball tack	> 12 (ball no.)
~ holding power	> 3 hours
~ service temp. range	-15 C to +60 C
Application	Optimum adhesion is achieved after a 24 hour bonding period in a constant ambient temperature of +23 C if:
	~ surfaces are clean, and free from grease and dust
	~ the tape is applied at temperatures between 0 C and +35 C
	~ contact with the exposed adhesive is avoided
	~ maximum pressure is used during application
	подписти в под пред пред пред пред пред пред пред пре
Storage and shelf life	Kept in clean, dry, well-ventilated conditions and an ambient temperature of +10 C to +30 C, the shelf life will be a minimum of 12 months
Packaging data	
~rolls per case	16
~ case weight	14kg