TECHNICAL DATA SHEET



SGS250 Silica Gel Sachets

Product description	Tyvek® sachets containing silica gel granules, used to remove humidity inside sealed packages to prevent corrosion, condensation, rusting and fungal growth. Ideal for electronics, precision equipment, pharmaceuticals, optics and leather goods
Product specifications	
~ sachet weight	250 g
~ quantity per packet	100
~ packet size	113 x 181 mm
~ packet weight	25.0 kg
Recommended use	It is recommended that silica gel sachets are used at a rate of 5g of
	silicα gel per cubic foot (0.028 m³)
	Ensure packaging is airtight for optimum protection
Technical data	
~ granule size	1.0-3.0 mm
~ moisture content	2.0% maximum @ 145°C
~ H₂O absorption @ 25°C	10% relative humidity = 6.5% w/w
	20% relative humidity = 12.0% w/w
	50% relative humidity = 27.0% w/w
	80% relative humidity = 36% w/w
~ pH	not less than 3.5
~ water soluble sulphates	1.0% maximum
~ water soluble chlorides	0.05% maximum
~ ammonia/ammonium	40
compounds	10 mg/kg maximum less than 125 micron = 0.5% maximum
~ friability and dust	less than 1.0 mm = 7.5% maximum
	areater than 3.0 mm = 7.5% maximum
	greater than 3.0 mm = 7.3% maximum
	The material conforms to BS 2540:1991 Granular Desiccant Silica Gel