



# LN150-B Packing Tape

<b>Product description</b>	<p>An excellent choice of polypropylene tape for the environmentally- and cost-conscious user, this low-noise tape features an unique 25mm core and an impressive roll length of 150 metres - more than twice the length of a standard 66 metre roll.</p> <p>This results in lower transportation costs and storage requirements, fewer stoppages for roll changing and increased productivity.</p>
<b>Product specifications</b>	
~ colour	buff
~ weight per roll	0.306 kg
~ width of roll	50mm
~ length of roll	150mtr
~ rolls per case	36
~ cases per pallet	60
~ dispenser code	BT50B
<b>Technical data</b>	
~ backing material	bi-axial oriented polypropylene film
~ adhesive	water based acrylic
~ film thickness	25mu (ASTMD-3652)
~ coating weight	22.0gsm (ASTMD-3652)
	note: +/- 6% tolerance on coating thickness is acceptable
~ initial tack	< 50mm (ASTMD-3121M)
~ peeling adhesion	7.60N/inch (high tack) (ASTMD-3330M)
~ shear value on steel	> 24 hours (ASTMD-3654M)
~ tensile strength	110.0N/inch (ASTMD-3759)
~ elongation at break	140% (ASTMD-3759)
~ application temperature	from +15C to -65C (optimum temperature +18 <sup>0</sup> C)
<b>Optimum storage</b>	<p>~ do not store for more than 6 months</p> <p>~ keep in original packaging, at +22<sup>0</sup>C, 50% humidity</p> <p>~ protect from extreme temperature, humidity and direct sunlight</p> <p>~ protect properly once removed from original packaging</p>

All information and recommendations are provided to the best of our knowledge, on the basis of our practical experience. Nevertheless we can make no warranties, expressed or implied, including but not limited to any implied warranty of merchantability or fitness for a particular purpose. The user is therefore responsible for determining whether the product is fit for a particular purpose and suitable for the user's method of application.