TECHNICAL DATA SHEET



LN150-C Packing Tape

Product description	An excellent choice of polypropylene tape for the environmentally- and cost-
	conscious user, this low-noise tape features an unique 25mm core and an
	impressive roll length of 150 metres - more than twice the length of a
	standard 66 metre roll.
	This results in lower transportation costs and storage requirements, fewer
	stoppages for roll changing and increased productivity.
Don't de la confliction	
Product specifications	
~ colour	clear
~ weight per roll	0.306 kg
~ width of roll	50mm
~ length of roll	150mtr
~ rolls per case	36
~ cases per pallet	60
~ dispenser code	BT50B
Technical data	
~ backing material	bi-axial oriented polypropylene film
~ adhesive	water based acrylic
~ film thickness	25mu (ASTMD-3652)
~ coating weight	22.0gsm (ASTMD-3652)
coucing weight	note: +/- 6% tolerance on coating thickness is acceptable
~ initial tack	< 50mm (ASTMD-3121M)
~ peeling adhesion	7.60N/inch (high tack) (ASTMD-3330M)
~ shear value on steel	> 24 hours (ASTMD-3654M)
~ tensile strength	110.0N/inch (ASTMD-3054M)
~ elongation at break	140% (ASTMD-3759)
~ application temperature	from +15C to -65C (optimum temperature +18°C)
~ application temperature	noin +13C to -03C (optimum temperature +18° C)
Optimum storage	~ do not store for more than 6 months
	~ keep in original packaging, at +22°C, 50% humidity
	~ protect from extreme temperature, humidity and direct sunlight
	~ protect properly once removed from original packaging